NSN 5320-00-530-6144

Mil-std (military Standard):

Mil-s-5626 spec.



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-530-6144 Fastener Length: Between 1.234 inches and 1.264 inches **Head Style:** Hexagon **Head Height:** 0.113 inches **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded mandrel **Grip Length:** Between 0.407 inches and 0.469 inches Width Across Flats: Between 0.332 inches and 0.346 inches Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel stem **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or ams 5639 assn standard 3rd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Passivate sleeve or cadmium sleeve **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response stem **Specification Data:** 80205-nas1673 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0