

View Online at <https://aerobasegroup.com/nsn/5320-00-531-9602>

Fastener Length:

0.694 inches

Head Style:

Hexagon

Head Height:

0.135 inches

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded mandrel

Grip Length:

Between 0.532 inches and 0.594 inches

Width Across Flats:

Between 0.367 inches and 0.375 inches

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Shear Strength:

9000 double pounds per square inch

Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

Material Specification:

Qq-s-764, comp 303 federal specification 1st material response sleeve or qq-s-764, comp 304 federal specification 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve or cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 military specification all treatment responses bolt

Specification Data:

80205-nas1669 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.