NSN 5320-00-534-7028

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-534-7028

Thread Class:

Thread Class:
3a
Fastener Length:
Between 0.378 inches and 0.398 inches
Head Style:
Flat fillister
Head Height:
Between 0.045 inches and 0.055 inches
Shank Diameter:
Between 0.166 inches and 0.169 inches
Head Major Diameter:
Between 0.274 inches and 0.294 inches
Expansion Device:
Threaded mandrel
Grip Length:
0.125 inches
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Shear Strength:
125000 single pounds per square inch
Special Features:
100 degrees countersinkin head
Material:
Steel comp 305 sleeve
Material Specification:
Qq-s-763 federal specification single material response sleeve
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response expander
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A040a0

NSN 5320-00-534-7028

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.