NSN 5320-00-538-6949

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-538-6949



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.645 inches and 0.665 inches

Head Style:

Err-090

Head Height:

Between 0.056 inches and 0.063 inches

Shank Diameter:

Between 0.2005 inches and 0.2025 inches

Shank Style:

Pin-rivet, multiple grooved

Head Major Diameter:

Between 0.288 inches and 0.302 inches

Grip Length:

Between 0.501 inches and 0.562 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

108000 single pounds per square inch

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-00-538-6949

Pin-rivet - Page 2 of 2

Fiig: A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

