

View Online at <https://aerobasegroup.com/nsn/5320-00-538-8288>

Fastener Length:

1.531 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.507 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 1.281 inches and 1.345 inches

Hardness Rating:

48.0 rockwell c and 53.0 rockwell c stem

Shear Strength:

5900 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 4027 or steel comp 4037 or steel comp 4130 sleeve

Material Specification:

66 federal standard 1st material response or astm a547 assn standard 2nd material response or 66 federal standard 3rd material response or mil-s-6758 military specification 3rd material response sleeve

Surface Treatment:

Cadmium and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl @2 federal specification all treatment responses sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.