

View Online at <https://aerobasegroup.com/nsn/5320-00-539-5148>

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.1870 inches and 0.1895 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.2578 inches and 0.3047 inches

**Grip Length:**

Between 0.062 inches and 0.125 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Criticality Code Justification:**

Aaze and aazg

**Heat Treatment:**

As fabricated

**Material:**

Steel comp 8740 or steel comp 8740 or steel comp 4140 or steel comp 4130 or steel comp 4340 or steel comp 8735 or steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 3135 or steel comp 4037

**Material Specification:**

Mil-s-6049 military specification 1st material response or ams 6322 assn standard 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6758 military specification 4th material response or ams 6415 assn standard 5th material response or mil-s-6098 military specification all material responses or mil-s-5000 military specification 6th material response or mil-s-5000 military specification 7th material response or mil-s-8503 military specification 8th material response or ams 6330 assn standard 9th material response or mil-s-8695 military specification 10th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Specification Data:**

80205-nas1055 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.