

View Online at <https://aerobasegroup.com/nsn/5320-00-541-1069>

Fastener Length:

Between 1.448 inches and 1.468 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.122 inches and 0.124 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.179 inches and 0.210 inches

Grip Length:

1.375 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Heat Treatment:

As fabricated

Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp 4340 or steel comp 4037 or steel comp 4130

Material Specification:

Mil-s-6098 uns g87350 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 uns g87400 assn standard 2nd material response or mil-s-8503 uns g61500 military specification 3rd material response or mil-s-5626 military specification 4th material response or ams6382 uns g41400 assn standard 4th material response or mil-s-5000 uns g43400 military specification 5th material response or mil-s-8695 uns g40370 military specification 6th material response or mil-s-6758 uns g41300 military specification 7th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Specification Data:

80205-nas1055 professional/industrial association standard and 73197-hs47 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.