NSN 5320-00-547-4177

View Online at https://aerobasegroup.com/nsn/5320-00-547-4177

Pin-rivet - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Fastener Length: Between 0.780 inches and 0.800 inches **Head Style:** Flush countersunk Width Between Flats: 0.094 inches **Shank Diameter:** Between 0.263 inches and 0.265 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.507 inches **Grip Length:** Between 0.689 inches and 0.750 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.216 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Hex socket head end, tension pull stem on thread end Material: Steel comp 8740 **Material Specification:** Aisi assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-00-547-4177

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0