

View Online at <https://aerobasegroup.com/nsn/5320-00-547-4180>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.780 inches and 1.800 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

0.094 inches

**Shank Diameter:**

Between 0.263 inches and 0.265 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.507 inches

**Grip Length:**

Between 1.689 inches and 1.750 inches

**Thready Qty Per Inch (tpi):**

48

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.216 inches

**Shear Strength:**

108000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Hex socket head end, tension pullstem on thread end

**Material:**

Steel comp 8740

**Material Specification:**

Aisi assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0