## NSN 5320-00-548-7038

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-548-7038



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.927 inches and 0.947 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.055 inches and 0.060 inches

#### Width Between Flats:

Between 0.064 inches and 0.065 inches

#### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.306 inches and 0.322 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

0.630 inches

## Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.164 inches

#### Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

## Thread Series Designator:

Unjc

#### Shelf Life:

N/a

# NSN 5320-00-548-7038

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

