NSN 5320-00-548-7178

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-548-7178 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.045 inches and 1.065 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol **Grip Length:** 0.505 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response or ams 5628 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-00-548-7178

Pin-rivet - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.