# NSN 5320-00-548-7184

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-548-7184

# Thread Class:

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 1.170 inches and 1.190 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

0.630 inches

## Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp 431

#### **Material Specification:**

Mil-s-18732 military specification single material response or ams 5628 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5320-00-548-7184

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

