NSN 5320-00-550-0756

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-550-0756

Head Style:

Flush countersunk

Shank Diameter:

Between 0.312 inches and 0.313 inches

Shank Style:

Err-090

Head Major Diameter:

0.429 inches

Grip Length:

Between 1.189 inches and 1.250 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-8695 military specification 5th material response or mil-s-6758 military specification all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.