NSN 5320-00-551-0158

Blind Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-s-5626 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-551-0158 **Head Style:** Hexagon **Head Height:** 0.160 inches Shank Diameter: Between 0.3095 inches and 0.3115 inches **Expansion Device:** Threaded stem **Grip Length:** Between 0.157 inches and 0.219 inches Width Across Flats: Between 0.429 inches and 0.437 inches Material: Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 303se boltsteel comp 4140 nut or steel comp 8740 nut or steel comp 303se nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve **Material Specification:** Mil-s-5626 military specification 1st material response bolt or mil-s-6049 military specification 2nd material response bolt or mil-s-6758 military specification 3rd material response boltmil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nutqq-s-763 federal specification 1st material response sleeve or ams 5631 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium bolt and chromate boltcadmium nut and chromate nutpassivate sleeve and cadmium sleeve **Surface Treatment Specification:** Qq-p-416 ty ii cl 2 federal specification single treatment response boltqq-p-416 ty ii cl 2 federal specification single treatment response nutmil-s-5002 military specification 1st treatment response sleeve and qq-p-416 ty i cl 3 federal specification 2nd treatment response sleeve Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0