NSN 5320-00-551-7980

Pin-rivet - Page 1 of 1

Mil-s-6098 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-551-7980 **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Shank Diameter: Between 0.155 inches and 0.157 inches **Shank Style: Head Major Diameter:** Between 0.242 inches and 0.262 inches **Grip Length:** Between 0.251 inches and 0.312 inches Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130 **Material Specification:** Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-5000 military specification 6th material response or mil-s-8695 military specification 7th material response or mil-s-6758 military specification 8th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A528u0 Mil-std (military Standard):