# NSN 5320-00-558-3079

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-558-3079

# Head Style:

Err-090

# Head Height:

Between 0.113 inches and 0.120 inches

### Shank Diameter:

Between 0.3730 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, multiple grooved

#### Head Major Diameter:

Between 0.549 inches and 0.565 inches

#### Grip Length:

Between 0.563 inches and 0.625 inches

#### **Features Provided:**

Casehardened

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

76.0 rockwell superficial 15-n and 81.0 rockwell superficial 15-n

#### Shear Strength:

21000 double pounds per square inch

# Material:

Steel comp 4037 or steel comp 4140 or steel comp 8740

# Material Specification:

Qq-w-405 federal specification all material responses

# Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Specification Data:**

80205-nas1452 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A528u0