NSN 5320-00-558-3123

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-558-3123

Fastener Length:

Between 2.060 inches and 2.260 inches

Head Style:

Err-090

Head Height:

Between 0.094 inches and 0.100 inches

Shank Diameter:

Between 0.3105 inches and 0.3120 inches

Shank Style:

Pin-rivet, multiple grooved

Head Major Diameter:

Between 0.455 inches and 0.471 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.251 inches and 0.312 inches

Features Provided:

Casehardened

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n

Shear Strength:

95000 single pounds per square inch

Material:

Steel comp 8740 or steel comp 4340 or steel comp 4140

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Specification Data:

80205-nas1450 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0