NSN 5320-00-558-3132

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-558-3132

view Offiline at https://aerobasegroup.com/hist//3520-00-550-5152
Fastener Length:
Between 2.190 inches and 2.390 inches
Head Style:
Err-090
Head Height:
Between 0.094 inches and 0.100 inches
Shank Diameter:
Between 0.3105 inches and 0.3120 inches
Shank Style:
Head Major Diameter:
Between 0.455 inches and 0.471 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.313 inches and 0.375 inches
Features Provided:
Casehardened
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n
Shear Strength:
95000 single pounds per square inch
Material:
Steel comp 8740 or steel comp 4340 or steel comp 4140
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification all treatment responses
Specification Data:
80205-nas1450 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A528u0