

View Online at <https://aerobasegroup.com/nsn/5320-00-558-4228>

**Fastener Length:**

Between 0.376 inches and 0.386 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.1880 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, multiple grooved

**Head Major Diameter:**

Between 0.263 inches and 0.305 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.126 inches and 0.188 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 8740 or steel comp 4340 or steel comp 4037

**Material Specification:**

Aisi assn standard all material responses or astm a547 assn standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Specification Data:**

80205-nas1436 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0