NSN 5320-00-559-6186

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-00-559-6186

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Grip Length:

Between 1.189 inches and 1.250 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-5000 military specification 6th material response or mil-s-8695 military specification 7th material response or mil-s-6758 military specification 8th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.

