## NSN 5320-00-559-7480

Solid Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-559-7480

| View Offline at https://defobasegroup.com/histr/3320-00-333-7-400  |
|--|
| Fastener Length:   |
| Between 0.365 inches and 0.385 inches  |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)                                   |
| Shank Diameter:  |
| Between 0.249 inches and 0.253 inches  |
| Shank Style:   |
| Straight w/radius chamfered tip  |
| Head Major Diameter:   |
| Between 0.472 inches and 0.480 inches  |
| Shear Strength:  |
| 33000 single pounds per square inch  |
| Countersink Angle:   |
| Between 99.5 degrees and 100.5 degrees   |
| Material:  |
| Aluminum alloy 2017  |
| Material Specification:  |
| Qq-a-430 federal specification single material response  |
| Surface Treatment:   |
| Anodize or oxide film  |
| Surface Treatment Specification:   |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |