

View Online at <https://aerobasegroup.com/nsn/5320-00-559-7851>

Fastener Length:

0.656 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Pull through hollow shank

Head Major Diameter:

0.339 inches

Expansion Device:

Plain stem-type t

Grip Length:

0.625 inches

Shear Strength:

415 single pounds per square inch

Countersink Angle:

120.0 degrees

Material:

Steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Cadmium mandrel or phosphate zinc mandrel or zinc mandrel

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response mandrel or mil-p-16232 ty z cl 2 military specification single treatment response mandrel or mil-c-16232 ty z cl 4 military specification single treatment response mandrel or qq-z-325 type 2 cl 3 federal specification single treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

spec.