

View Online at <https://aerobasegroup.com/nsn/5320-00-559-7851>

**Fastener Length:**

0.656 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.186 inches and 0.190 inches

**Shank Style:**

Pull through hollow shank

**Head Major Diameter:**

0.339 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

0.625 inches

**Shear Strength:**

415 single pounds per square inch

**Countersink Angle:**

120.0 degrees

**Material:**

Steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel

**Material Specification:**

Qq-a-430 federal specification single material response body

**Surface Treatment:**

Cadmium mandrel or phosphate zinc mandrel or zinc mandrel

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response mandrel or mil-p-16232 ty z cl 2 military specification single treatment response mandrel or mil-c-16232 ty z cl 4 military specification single treatment response mandrel or qq-z-325 type 2 cl 3 federal specification single treatment response mandrel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

spec.