

View Online at <https://aerobasegroup.com/nsn/5320-00-559-8516>

**Fastener Length:**

Between 0.731 inches and 0.761 inches

**Head Style:**

Hexagon countersunk

**Head Height:**

Between 0.072 inches and 0.079 inches

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film or wax

**Grip Length:**

Between 0.531 inches and 0.594 inches

**Width Across Flats:**

Between 0.332 inches and 0.346 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Shear Strength:**

3100 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Heat Treatment:**

Annealed

**Material:**

Aluminum alloy 7075 body

**Material Specification:**

Qq-a-225/9 federal specification single material response body

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.