## NSN 5320-00-559-8516

Blind Rivet - Page 1 of 2

A040a0



View Online at https://aerobasegroup.com/nsn/5320-00-559-8516

Fastener Length:
Between 0.731 inches and 0.761 inches
Head Style:
Hexagon countersunk
Head Height:
Between 0.072 inches and 0.079 inches
Shank Diameter:
Between 0.197 inches and 0.199 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Expansion Device:
Serrated stem-type w
Lubrication:
Dry film or wax
Grip Length:
Between 0.531 inches and 0.594 inches
Width Across Flats:
Between 0.332 inches and 0.346 inches
Min. Tensile Strength (psi):
180000 pounds per square inch
Shear Strength:
3100 double pounds per square inch
Countersink Angle:
100.0 degrees
Heat Treatment:
Annealed
Material:
Aluminum alloy 7075 body
Material Specification:
Qq-a-225/9 federal specification single material response body
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

## NSN 5320-00-559-8516

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.