

View Online at <https://aerobasegroup.com/nsn/5320-00-562-7398>

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.1625 inches and 0.1645 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Grip Length:

Between 0.595 inches and 0.656 inches

Width Across Flats:

Between 0.244 inches and 0.250 inches

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Shear Strength:

3355 double pounds per square inch

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve or steel comp 304 sleeve

Material Specification:

Mil-s-5676 military specification single material response stem or mil-s-6049 military specification single material response stem or mil-s-6758 military specification single material response stem

Surface Treatment:

Passivate sleeve or cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response stem

Specification Data:

80205-nas1699 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5676 spec.