## NSN 5320-00-576-2221



Pin-rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-576-2221 Fastener Length: Between 1.491 inches and 1.501 inches **Head Style:** Flush countersunk Shank Diameter: Between 0.2480 inches and 0.2495 inches **Shank Style:** Pin-rivet, multiple grooved **Head Major Diameter:** Between 0.346 inches and 0.399 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.189 inches and 1.250 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 77.2 rockwell superficial 15-n and 82.0 rockwell superficial 15-n **Shear Strength:** 850000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 or steel comp 4340 or steel comp 4037 **Material Specification:** Aisi assn standard all material responses or astm a547 assn standard all material responses **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Specification Data:** 80205-nas1438 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A528u0