## NSN 5320-00-579-5874

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-579-5874

| •  |
|--|
| Fastener Length:   |
| Between 2.116 inches and 2.146 inches  |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter:  |
| Between 0.258 inches and 0.260 inches  |
| Shank Style:   |
| Threaded self-plugging shank w/sleeve  |
| Head Major Diameter:   |
| 0.463 inches   |
| Expansion Device:  |
| Threaded mandrel   |
| Grip Length:   |
| Between 1.345 inches and 1.406 inches  |
| Hardness Rating:   |
| 39.0 rockwell c and 43.0 rockwell c  |
| Shear Strength:  |
| 9000 double pounds per square inch   |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Heat Treatment:  |
| As fabricated  |
| Material:  |
| Steel  |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 2 federal specification single treatment response             |
| Specification Data:  |
| 80205-nas1670 professional/industrial association standard                         |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |