

View Online at <https://aerobasegroup.com/nsn/5320-00-582-3288>

Fastener Length:

0.170 inches

Head Style:

Universal

Head Height:

Between 0.054 inches and 0.064 inches

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.238 inches and 0.262 inches

Expansion Device:

Serrated stem-type w

End Application:

W/s: helicopter, advance attack, ah-1w; helicopter, hh-53h pave low; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; helicopter, mh-53e; u-2 airframe; air conditioner, 60hz 9000btu; defense meteorological satellite program (dmsp); air conditioner, 30hz 1800btu

Grip Length:

0.062 inches

Special Features:

W/special pulling head

Material:

Aluminum alloy 2017 stem

Material Specification:

Qq-a-430 federal specification single material response stem

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.