# NSN 5320-00-582-3501

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-582-3501

# Fastener Length:

0.232 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.124 inches and 0.128 inches

#### Shank Style:

Self-plugging

#### Head Major Diameter:

Between 0.221 inches and 0.229 inches

## Expansion Device:

Serrated stem-type w

#### Grip Length:

Between 0.063 inches and 0.125 inches

#### Shear Strength:

240 single pounds per square inch

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Special Features:

W/special pulling head

#### Material:

Aluminum alloy 2017 stem

#### Material Specification:

Qq-a-430 federal specification single material response stem

# Surface Treatment:

Anodize stem or chromate stem

# Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

Shelf Life:

N/a

# Unit Of Measure:

```
---
```

# Demilitarization:

No

# Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.