

View Online at <https://aerobasegroup.com/nsn/5320-00-589-4190>

**Fastener Length:**

1.471 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.309 inches and 0.311 inches

**Head Major Diameter:**

Between 0.626 inches and 0.635 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.532 inches and 0.594 inches

**Min. Tensile Strength (psi):**

3600 pounds per square inch

**Shear Strength:**

12000 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Heat Treatment:**

As fabricated

**Material:**

Steel comp 8740 body or steel comp 4130 body or steel comp 4140 body

**Material Specification:**

Mil-s-6049 military specification 1st material response body or mil-s-6758 military specification 2nd material response body or mil-s-5626 military specification 3rd material response body

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.