

View Online at <https://aerobasegroup.com/nsn/5320-00-598-9516>

Fastener Length:

0.290 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

0.094 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.172 inches and 0.192 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.101 inches and 0.200 inches

Shear Strength:

125 single pounds per square inch

Countersink Angle:

Between 118.5 degrees and 121.5 degrees

Material:

Steel comp 1006 stem or steel comp 1008 stem or steel comp 1010 stem or steel comp 1011 stem or steel comp 1012 stem or steel comp 1013 stem or steel comp 1015 stem or steel comp 1016 stem or steel comp 1017 stem or steel comp 1018 stem or steel comp 1019 stem or steel comp 1020 stem or steel comp 1021 stem or steel comp 1022 stem or steel comp 1023 stem or steel comp 1025 stem

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Zinc stem and chromate stem or cadmium stem or cadmium stem and chromate stem or cadmium stem and phosphate stem or phosphate stem

Surface Treatment Specification:

Qq-z-325, type 2, cl3 federal specification 1st treatment response stem and qq-p-416 type 1 federal specification 2nd treatment response stem or qq-p-416 type 2 federal specification 3rd treatment response stem or qq-p-416 type 3 federal specification 4th treatment response stem or mil-p-16232 ty z cl 2 or cl 3 military specification 5th treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.