NSN 5320-00-603-2533

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-603-2533 **Head Style:** Hexagon **Head Height:** 0.135 inches **Shank Diameter:** Between 0.258 inches and 0.260 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** Between 1.157 inches and 1.219 inches Width Across Flats: Between 0.367 inches and 0.375 inches Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Shear Strength: 9000 single pounds per square inch Material: Steel comp 304 stem or steel stem or steel comp 303 stem **Material Specification:** Qq-s-763 federal specification 1st material response stem or ams 5639 assn standard 2nd material response stem or ams 5641 assn standard 2nd material response stem or astm 582 assn standard 3rd material response stem **Surface Treatment:** Passivate sleeve or cadmium sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response stem **Specification Data:** 80205-nas1669 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.