

View Online at <https://aerobasegroup.com/nsn/5320-00-613-7958>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.503 inches and 0.523 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

End Application:

Helicopter observation (ahip), oh-58d; aircraft, eagle f-15; aircraft, phantom f-4; aircraft, stratolifter c-135; aircraft, orion p-3; aircraft, f-16; aircraft, harrier av-8b; joint stars target radar system; aircraft, b-1b; aircraft, galaxy c-5

Grip Length:

0.193 inches

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0