

View Online at <https://aerobasegroup.com/nsn/5320-00-616-0379>

**Fastener Length:**

0.295 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Self-plugging

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

W/s: radar set, lightweight 3d (an/tps-59); airborne mobile dir air spt ctl (2id), (02mjul83)(an/uyq-3a); helicopter, mh-53e; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); helicopter, carrier based asw, sh-60f; support equipment, b-1 aircraft; missile, air intercept, sidewinder (aim-9); helicopter, advance attack, ah-1w; aircraft, awacs, e-3a; helicopter, search and rescue, hh-60h

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Shear Strength:**

230 single pounds per square inch

**Countersink Angle:**

101.0 degrees

**Special Features:**

Sleeve dyed orange, w/special pulling head

**Material:**

Aluminum alloy 2017 stem

**Material Specification:**

Qq-a-430 federal specification single material response stem

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.