

View Online at <https://aerobasegroup.com/nsn/5320-00-616-0379>

Fastener Length:

0.295 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Expansion Device:

Serrated stem-type w

End Application:

W/s: radar set, lightweight 3d (an/tps-59); airborne mobile dir air spt ctl (2id), (02mjul83)(an/uyq-3a); helicopter, mh-53e; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); helicopter, carrier based asw, sh-60f; support equipment, b-1 aircraft; missile, air intercept, sidewinder (aim-9); helicopter, advance attack, ah-1w; aircraft, awacs, e-3a; helicopter, search and rescue, hh-60h

Grip Length:

Between 0.126 inches and 0.187 inches

Shear Strength:

230 single pounds per square inch

Countersink Angle:

101.0 degrees

Special Features:

Sleeve dyed orange, w/special pulling head

Material:

Aluminum alloy 2017 stem

Material Specification:

Qq-a-430 federal specification single material response stem

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.