

View Online at <https://aerobasegroup.com/nsn/5320-00-616-7321>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.510 inches and 2.530 inches

Head Style:

Err-090

Head Height:

0.063 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.384 inches and 0.416 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Grip Length:

Between 2.120 inches and 2.130 inches

Thread Size:

0.250 inches

Shear Strength:

12260 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 431

Material Specification:

Ams5628 assn standard single material response or mil-s-18732 military specification single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.