

View Online at <https://aerobasegroup.com/nsn/5320-00-623-6366>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.683 inches and 1.708 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.3403 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

0.508 inches

**Tip Diameter:**

0.3163 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 1.302 inches and 1.317 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.3125 inches

**Shear Strength:**

108000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Criticality Code Justification:**

Feat

**Special Features:**

0.138-32unj-3bthreaded concentric hole along the longitudinal centerline of head end 0.300 in. Min, 0.345 in. Maximum dp, 0.120 in. Slot lg, 0.060 in. Slot w located 0.360 in. From top of head to beginning of slot

**Material:**

Steel comp 8740 or steel comp e4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.