

View Online at <https://aerobasegroup.com/nsn/5320-00-623-6369>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.4330 inches and 2.4580 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.3547 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.4720 inches and 0.5220 inches

**Tip Diameter:**

0.3150 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 2.0520 inches and 2.0670 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3125 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Slot included

**Material:**

Steel comp 8740 bolt or steel comp e4340 bolt

**Material Specification:**

Mil-s-6049 military specification 1st material response bolt or mil-s-5000 military specification 2nd material response bolt

**Surface Treatment:**

Cadmium bolt and chromate bolt

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification single treatment response bolt

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.