

View Online at <https://aerobasegroup.com/nsn/5320-00-623-6370>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.9330 inches and 0.9580 inches

Head Style:

Flush countersunk

Shank Diameter:

0.3260 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.4440 inches and 0.4940 inches

Tip Diameter:

0.3176 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.5520 inches and 0.5670 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.3125 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Slot included

Material:

Steel comp 8740 bolt or steel comp e4340 bolt

Material Specification:

Mil-s-6049 military specification 1st material response bolt or mil-s-5000 military specification 2nd material response bolt

Surface Treatment:

Cadmium bolt and chromate bolt

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response bolt

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.