

View Online at <https://aerobasegroup.com/nsn/5320-00-629-2874>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.440 inches and 1.460 inches

Head Style:

Err-090

Head Height:

Between 0.078 inches and 0.088 inches

Width Between Flats:

0.156 inches

Shank Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Grip Length:

0.880 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

16000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

One collar included

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Material Specification:

Mils-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, class 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.