NSN 5320-00-637-5124

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-637-5124

Fastener Length:
Between 1.088 inches and 1.118 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.197 inches and 0.199 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.385 inches
Expansion Device:
Threaded mandrel
Grip Length:
Between 0.970 inches and 1.031 inches
Countersink Angle:
100.0 degrees
Material:
Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut
Material Specification:
Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military
specification 3rd material response nut
Surface Treatment:
Passivate sleeve or cadmium sleeve
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response nut
Specification Data:
80205-nas1670 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-s-6758 spec.