

View Online at <https://aerobasegroup.com/nsn/5320-00-637-5357>

Fastener Length:

0.569 inches

Head Style:

Hexagon

Head Height:

0.135 inches

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded mandrel

Grip Length:

Between 0.407 inches and 0.469 inches

Width Across Flats:

Between 0.367 inches and 0.375 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Shear Strength:

9000 double pounds per square inch

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a4572 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve

Specification Data:

80205-nas1669 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.