# NSN 5320-00-637-6284

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-637-6284

## Fastener Length:

Between 0.618 inches and 0.638 inches

#### Head Style:

Flush countersunk

# Shank Diameter:

Between 0.188 inches and 0.189 inches

# Shank Style:

Stump

#### Head Major Diameter:

Between 0.344 inches and 0.386 inches

#### Grip Length:

Between 0.345 inches and 0.406 inches

## **Features Provided:**

Casehardened

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

37.0 rockwell c and 41.0 rockwell c

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

# Material:

Steel comp 4037 or steel comp 4140 or steel comp 8740 or steel comp 4340

# Material Specification:

Qq-w-405 federal specification all material responses

#### Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Specification Data:**

80205-nas1486 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# Fiig:

A528u0