

View Online at <https://aerobasegroup.com/nsn/5320-00-658-3842>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.503 inches and 0.523 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

End Application:

W/s: ticonderoga class cg (47); missile, all-weather anti-ship, harpoon (agm-84); aircraft, awacs, e-3a; engine, aircraft, tf-33-p-7 (c-141a/b); aircraft, eagle f-15; aircraft, hx unique; aircraft, hornet f/a-18; aircraft, harrier av-8b

Grip Length:

0.193 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0