

View Online at <https://aerobasegroup.com/nsn/5320-00-676-8252>

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.1625 inches and 0.1645 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.094 inches and 0.156 inches

Width Across Flats:

Between 0.277 inches and 0.283 inches

Material:

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 boltaluminum alloy 7075 nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve

Material Specification:

Mil-s-5626 military specification 1st material response bolt or mil-s-6049 military specification 2nd material response bolt or mil-s-6758 military specification 3rd material response boltqq-a-225/9 federal specification single material response nutqq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium bolt and chromate boltanodize nutpassivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416 ty ii cl 2 federal specification single treatment response boltmil-a-8625 ty ii military specification single treatment response nutmil-s-5002 military specification 1st treatment response sleeve and qq-p-416 ty icl 3 federal specification 2nd treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.