NSN 5320-00-677-2609

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-677-2609 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.802 inches and 0.822 inches **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.162 inches and 0.163 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches **Grip Length:** Between 0.495 inches and 0.505 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-00-677-2609

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.