NSN 5320-00-677-2800

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-677-2800



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.677 inches and 0.697 inches

Head Style:

Err-090

Head Height:

Between 0.037 inches and 0.047 inches

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.162 inches and 0.163 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Grip Length:

Between 0.370 inches and 0.380 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-00-677-2800

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

