# NSN 5320-00-680-4456

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-680-4456

## Fastener Length:

Between 2.310 inches and 2.510 inches

#### Head Style:

Err-090

## Head Height:

Between 0.099 inches and 0.111 inches

### Shank Diameter:

Between 0.1880 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, multiple grooved

### Head Major Diameter:

Between 0.297 inches and 0.327 inches

### Lubrication:

Cetyl alcohol

### Grip Length:

Between 0.532 inches and 0.594 inches

## **Features Provided:**

Casehardened

#### Hardness Rating:

77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n

## Shear Strength:

95000 single pounds per square inch

#### Material:

Steel comp 8740 or steel comp 4340 or steel comp 4140

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

#### **Specification Data:**

80205-nas1466 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A528u0