

View Online at <https://aerobasegroup.com/nsn/5320-00-688-0108>

**Fastener Length:**

Between 3.440 inches and 3.640 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.310 inches and 0.312 inches

**Shank Style:**

Pin-riquet, multiple grooved

**Head Major Diameter:**

Between 0.416 inches and 0.479 inches

**Grip Length:**

Between 1.939 inches and 2.000 inches

**Features Provided:**

Casehardened

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

37.0 rockwell c and 41.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 4037

**Material Specification:**

Astm a547 military specification all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Specification Data:**

80205-nas1440 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

spec.